

## TRACTOR ATTACHMENTS

TRACTOR	MAX 22 4WD HST	MAX 25 4WD HST	MAX 28XL 4WD HST	MAX 28XL 4WD Shuttle
<b>LOADER</b>	ML202		ML205	
Maximum Lift Height	75"		82.7"	
Clearance with Attachment Dumped	60"		67.3"	
Reach at Maximum Height	23"		29"	
Maximum Dump Angle	38°		32°	
Attachment Rollback Angle	20°		24°	
Digging Depth Below Grade	4"		2.6"	
Lift Capacity to Full Height @ Pivot Pins	900		1402	
Breakout Force @ Pivot Pins	2000		2690	
Rated Flow (Tractor System)	4.6 gpm		4.6 gpm	
Attachment Width	50"		48"	
Attachment Rated Capacity	5.3 cu. ft.		7 cu. ft.	
Cycle Times @ rpm	2500		2600	
Raise Boom (seconds)	4.3		3.3	
Lower Boom (seconds)	3.5		2.4	
Dump Attachment (seconds)	2.8		2.2	
Retract Attachment (seconds)	2.5		2.6	
<b>BACKHOE MODEL</b>	MB60A		MB63A	
<b>TRANSPORT</b>				
Transport Height (maximum)	66"		70"	
Transport Overhang	38"		37"	
<b>OPERATIONAL</b>				
Maximum Digging Depth	80"		76.3"	
Digging Depth (2 Ft.) Flat Bottom	77"		74.9"	
Overall Operating Height - Fully Raised	93"		104.8"	
Loading Height (bucket at 60°)	60"		62"	
Loading Reach (bucket at 60°)	39"		36"	
Reach From Swing Post	98"		102"	
Bucket Rotation	185°		180°	
Swing Arc	140°		150°	
Stabilizer Spread Operating Position	86"		74"	
Stabilizer Down Below Grade	10"		6"	
System Relief Valve Setting (psi)	2050		2000	
Digging Force - Bucket (lbs.)	2050		2145	
Digging Force - Dipper (lbs.)	1256		903	

## TRACTOR SPECIFICATIONS



TRACTOR	MAX 22 4WD	MAX 25 4WD	MAX 28XL 4WD	MAX 28XL 4WD
<b>ENGINE</b>	HST	HST	HST	Shuttle
Type	Four stroke, indirect injection water-cooled diesel			
Cylinders	3			
Engine HP (kW) @ rpm	22 (16.4) @ 2500	25 (18.6) @ 2500	28 (20.8) @ 2600	
Compression Ratio	22:1			
Displacement cubic inch <sup>3</sup> (cc)	68.6 (1125)	80.4 (1318)		
Fuel Tank Capacity	6.1 gallons			
<b>ELECTRICAL</b>				
Battery Capacity	12 volt, 46 amp hours		12 volt, 35 amp hours	
Alternator	12 volt, 50 amp hours			
<b>CLUTCH</b>				
Type	Single plate, dry			
<b>TRANSMISSION</b>				
Type	HST - 2 ranges			Constant mesh on gear shift and synchro mesh on F/R shuttle
Number of Gears / Speeds	Infinite			8F / 8R
Max Speed Forward / Reverse mph (kmph)	9.6 (15.5) / 4.9 (7.9)		9.7 (15.6) / 5.1 (8.2)	10.9 (17.6) / 9.1 (14.8)
<b>STEERING</b>				
Type	Hydrostatic Power			
Pump Output (gallons per minute)	2.7			
<b>BRAKES</b>				
Type	Wet disc			
<b>HYDRAULIC SYSTEM</b>				
Type	Open center, full live hydraulic with position control			
Pump Output (gallons per minute)	4.6			
3-Point Linkage	Category 1, with check chains			
Lift Capacity (lbs.)	1400		2205	
Rear Auxiliary Remote Valves	1 spool optional			
<b>PTO</b>				
Type	Live		Trans	
PTO RPM (engine rpm)	540 @ 2376			
Mid PTO RPM (engine rpm)*	2000 @ 2556		2000 @ 2526	
PTO HP (kW)	16 (11.9)	20 (14.9)	22 (16.4)	23.5 (17.5)
<b>OPERATING WEIGHT</b>				
Total (lbs.)	1693		1863	1819
<b>DIMENSIONS with Ag Tires</b>				
Overall Length Inches (mm)	104.1 (2645)		109.3 (2775)	
Overall Width Inches (mm)	50.7 (1290)		54.3 (1380)	
Overall Height Inches (mm) (with Industrial Tires)	81.5 (2070)		84.3 (2140)	
Turning Radius Min. Feet (meters)	7.2 (2.2)		6.6 (2.0)	
<b>TIRES Sizes and Options</b>				
Ag (Front / Rear)	6x12 / 9.5x16		7x12 / 9.5x16	
Industrial (Front / Rear)	20x8-10 / 27x12.5-15		23x8.5-12 - 12x16.5	
Turf (Front / Rear)	20x8-10 / 29x12.5-15		23x8.5-12 / 33x12.5-16.5	

# Max Series

**SUPERIOR  
PERFORMANCE  
DAY IN AND  
DAY OUT**



Max 22 HST



Max 25 HST



Max 28XL Shuttle

9020 JACKRABBIT RD., Suite 600 • Houston, Texas 77095 • 877-449-7771

**MahindraUSA.com • MahindraCanada.ca**  
© 2013 Mahindra USA MAH-0413 MAH51XXXX



#1 Selling Tractor in the World

**Mahindra**  
Rise.

**AVAILABLE IMPLEMENTS**

**VERSATILITY -  
Max Series**

Industry-redefining sub-compact and mid-compact models. The backbone of all Max series tractors is a full-length tractor frame that will allow users to install a backhoe at any time. The Max series have a wide range of attachments and implements, including a driver-over mowing deck, snow blowers, blades, brooms and feature the highest capacity loaders in the market.

**Key Features:**

- Max Versatility - Choose up to 15 implements to handle any task
- Max Maneuverability - Best in class turning radius to get work done in tight spaces
- Max Comfort - Easy turn seat for Tractor - Loader - Backhoe operation, easy on and off with an open platform.
- Max Stability - Tractor tires, better traction, stability and safety for all jobs
- Max Lift Capacity - Lift more, carry more, pull more and get more done
- Max Engine Performance - 28% lower RPM results in smooth, quiet operation and less fuel consumption
- 5 year power train warranty

**Ideal For:**

- Specialty / Hobby Farming
- Rural Lifestyle
- Equine
- Home
- Grounds Maintenance / Municipal



Engine - right side view

- Easy access to engine and maintenance items
- Lower rated engine rpm, means longer life, less noise, and better fuel efficiency
- Powerful and reliable Mitsubishi engine



Dash panel

- Clear view, easy-to-read instrument panel
- Brilliant backlighting
- Colorful warning lights that quickly inform the operator when service is required



Mower

- Drive over deck for easy installation and removal
- Excellent cutting quality
- Available mulch kit

**SUPERIOR PERFORMANCE. GREATER VALUE.**

- Superior lift capacity = Lift heavier loads
- 5 year warranty = Peace of mind
- Professional grade construction = Bigger, thicker, more solid components
- Heavier, sturdier chassis = Greater traction, stability & safety



Mahindra offers a huge selection of implements to help you accomplish whatever task you wish to tackle and provide a complete Mahindra experience.

- Wide array of implements (186 variations)
- Competitive financing terms
- Standard-, Medium-, and Heavy-Duty implements to meet your needs
- Implements feature rugged construction with heavy-duty components
- 5 year gearbox limited warranty
- SNOW BLOWERS and SNOW REMOVAL equipment to meet cold-weather needs
- BEST VALUE in the market today

